



STRAIGHT	Type	Material	Width (mm)	Height (mm)	Pulley diameter (mm)	Colour ¹
	BR25	PVC	54	25	80	green, black, blue, white
	BR30	PVC	54	30	80	green, black, blue, white
	BR40	PVC	54	40	80	green, black, blue, white
	BR50	PVC	54	50	80	green, black, blue, white
	BR60	PVC	54	60	80	green, black, blue, white
	BR75	PVC	54	75	80	green, black, blue, white
	BR80	PVC	54	80	80	green, black, blue, white
	BR90	PVC	54	90	80	green, black, blue, white
	BR100	PVC	54	100	80	green, black, blue, white
	BR110	PVC	54	110	80	green, black, blue, white
	BR120	PVC	54	120	80	green, black, blue, white
	BENT	Type	Material	Width (mm)	Height (mm)	Pulley diameter (mm)
BK40		PVC	54	40	80	green, black, blue, white
BK50		PVC	54	50	80	green, black, blue, white
BK60		PVC	54	60	80	green, black, blue, white
BK75		PVC	54	75	80	green, black, blue, white
BK80		PVC	54	80	80	green, black, blue, white
BK90		PVC	54	90	80	green, black, blue, white
BK100	PVC	54	100	80	green, black, blue, white	

¹ The colours white and blue meet EU and FDA guidelines for food contact.

PU on page 2

STRAIGHT	Type	Material	Width (mm)	Height (mm)	Pulley diameter (mm)	Colour ¹
	BUR25	PU	54	25	80	blue, white
	BUR30	PU	54	30	80	blue, white
	BUR40	PU	54	40	80	blue, white
	BUR50	PU	54	50	80	blue, white
	BUR60	PU	54	60	80	blue, white
	BUR75	PU	54	75	80	blue, white
	BUR80	PU	54	80	80	blue, white
	BUR90	PU	54	90	80	blue, white
	BUR100	PU	54	100	80	blue, white
	BUR110	PU	54	110	80	blue, white
	BUR120	PU	54	120	80	blue, white
BENT	Type	Material	Width (mm)	Height (mm)	Pulley diameter (mm)	Colour ¹
	BUK40	PU	54	40	80	blue, white
	BUK50	PU	54	50	80	blue, white
	BUK60	PU	54	60	80	blue, white
	BUK75	PU	54	75	80	blue, white
	BUK80	PU	54	80	80	blue, white
	BUK90	PU	54	90	80	blue, white
BUK100	PU	54	100	80	blue, white	

¹ The colours white and blue meet EU and FDA guidelines for food contact.

Standard length of each cleat is 2 metres for straight cleats and 1.2 metres for bent cleats.

Apart from the standard fabric-reinforced cleats listed above, which are available both loose and fitted on a conveyor belt, we can also produce belts with special fabric-reinforced cleats, e.g.:

- with diamond profile (to prevent material from sticking to the cleat)
- straight or bent fabric-reinforced cleats higher than 120mm (for instance our special cleat BK225 (see picture))
- fabric-reinforced PU cleats