

## Tolerances for fabricated conveyor belts

Open conveyor belt (not endless)		Tolerance BTE (mm)
Width (mm)		
0	to 300	± 2
300	to 400	± 2
400	to 500	± 2
500	to 600	± 2
600	to 650	± 2
650	to 800	± 2
800	to 1,000	± 2
1,000	to 1,200	± 3
1,200	to 1,400	± 3
1,400	to 1,600	± 3
1,600	to 1,800	± 3
1,800	to 2,000	± 3
2,000	to 2,200	± 5
2,200	to 2,400	± 5
2,400	to 2,600	± 5
2,600	to 2,800	± 5
2,800	to 3,000	± 5
3,000	to 3,200	± 5

Length	Tolerance BTE
1 length	2.5%
Multiple lengths	5.0%
Sum of several lengths	2.5%

Endless conveyor belt		Tolerance BTE (mm)
Length (mm)		
0	to 15,000	± 50
15,000	to 20,000	± 75
20,000	+	± 0.5% of total length

Assembled conveyor belt		Tolerance BTE (mm)
Width		± 2% (max. ± 2 mm)
Length		+ 8%, - 1% (max. 100 mm)

Thickness of conveyor belt		Tolerance BTE (mm)
Up to 1.6 mm thickness		+ 0.10 mm to - 0.10 mm
1.7 mm to 2.0 mm thickness		+ 0.20 mm to - 0.10 mm
2.1 mm to 3.5 mm thickness		+ 0.25 mm to - 0.15 mm
3.6 mm to 6.5 mm thickness		+ 0.30 mm to - 0.20 mm
6.6 mm and thicker		+ 0.30 mm to - 0.30 mm

**Do you need a product with even smaller tolerances? This can be arranged in mutual consultation. Special restrictions may apply to conveyor belts with particular accessories or unusual belt designs, these tolerances are available on request. It will be our pleasure to discuss your special wishes.**

Do you have questions about our tolerances, or are you looking for a special conveyor belt? Feel free to contact us via +31 (0) 251 319 119 or [info@bandtransporteurope.nl](mailto:info@bandtransporteurope.nl).

\*Bandtransport Europe reserves the right to make changes to the published tolerances without prior announcement.