



Belt Construction

Type 11-31M anthracite

Fabric	
Number of fabrics	1
Fabric top layer	Polyester multifilament
Fabric inner layer	E
Fabric bottom side	-
	-
	-

Cover			Bottomside		
Thickness cover	0,6 mm	0,024 inch	Thickness bottom side	0,6 mm	0,024 inch
Material top side		PVC	Material bottom side		PVC
Profile top side		-	Profile bottom side		Big Diamond (3 mm)
Hardness top layer (° ShoreA)		80			

Technical data

Coefficient of friction (steel)		0,35	Tension force for 1% elongation	8 N/mm	45,7 lbf/inch
Thickness	2 mm	0,079 inch	Maximum tension	12 N/mm	68,5212 lbf/inch
Weight	1,9 kg/m ²	0,39 lb/ft ²	Maximum strain		1,6 %
Recommended tension	3-6 N/mm	17-34 lbf/inch			
Recommended tension: strain		0,4-0,7 %			

Rol

Carrying rollers	Yes	Minimum pulley diameter flection	35 mm	1,38 inch
Slider bed	Limited	Minimum pulley diameter contraflect	50 mm	1,97 inch
Throughed installation	Yes			

International standards

FDA conformance	No	EU conformance	No
USDA conformance	No	ATEX conformance	No

Properties

Oil and grease resistant	Limited		Maximum	90 °C	194 °F
Antistatic cover	Yes		Minimum	-15 °C	5 °F
Antistatic fabric	No				
Flame retardant	No				
Lateral stable	No				
Color	anthracite				

Last modification on: 23-12-2010