

## Belt Construction

### Type 22-13 green

Fabric	
Number of fabrics	2
Fabric top layer	Polyester monofilament, with lateral stability R
Fabric inner layer	-
Fabric bottom side	Polyester monofilament, with lateral stability R

Cover			Bottomside		
Thickness cover	2 mm	0,079 inch	Thickness bottom side	0,6 mm	0,024 inch
Material top side		PVC	Material bottom side		PVC
Profile top side		-	Profile bottom side		Big Diamond (3 mm)
Hardness top layer (° ShoreA)		60			

## Technical data

Coefficient of friction (steel)		0,35	Tension force for 1% elongation	10 N/mm	57,1 lbf/inch
Thickness	4,55 mm	0,2 inch	Maximum tension	20 N/mm	114,2 lbf/inch
Weight	5,1 kg/m <sup>2</sup>	1,04 lb/ft <sup>2</sup>	Maximum strain		2,3 %
Recommended tension	4-6 N/mm	22-34 lbf/inch			
Recommended tension: strain		0,4-0,7 %			


## Rol

Carrying rollers	Yes	Minimum pulley diameter flection	80 mm	3,15 inch
Slider bed	Limited	Minimum pulley diameter contraflect	140 mm	5,51 inch
Throughed installation	No			

## International standards

FDA conformance	No	EU conformance	No
USDA conformance	No	ATEX conformance	No

## Properties

Oil and grease resistant	Limited		Maximum	90 °C	194 °F
Antistatic cover	Yes		Minimum	-15 °C	5 °F
Antistatic fabric	No				
Flame retardant	No				
Lateral stable	Yes				
Color	green				

Last modification on: 23-12-2010