

Belt Construction

Fabric

Number of fabrics

Fabric top layer

Polyester monofilament, with lateral stability

R

Fabric inner layer

Polyester monofilament, with lateral stability

R

Fabric bottom side

Polyester monofilament, with lateral stability

R

Fabric bottom side

Polyester monofilament, with lateral stability

R

Type 32-11 green

Cover			Bottomside	Bottomside			
Thickness cover	0,7 mm	0,028 inch	Thickness bottom side	0,6 mm	0,024 inch		
Material top side		PVC	Material bottom side		PVC		
Profile top side		-	Profile bottom side	Big Diamond	Big Diamond (3 mm)		
Hardness top layer ((° ShoreA)		80					

Technical data

Coefficient of friction (steel)		0,35	Tension force for 1% elongation	13 N/mm	74 lbf/inch
Thickness	4,6 mm	0,181 inch	Maximum tension	30 N/mm	171 lbf/inch
Weight	5,1 kg/m ²	1,04 lb/ft²	Maximum strain		2,5 %
Recommended tension	5-8 N/mm	28-45 lbf/inch			
Recommended tension: strain		0,4-0,7 %			

Rol

Carrying rollers	Yes	Minimum pulley diameter flection	80 mm	3,15 inch
Slider bed	Limited	Minimum pulley diameter contraflect	140 mm	5,51 inch
Throughed installation	No			

International standards

FDA conformance	No	EU conformance	No
USDA conformance	No	ATEX conformance	No

Properties

Oil and grease resistant	Limited	ćU			
Antistatic cover	Yes	χ. Ιχ.	Maximum	90 °C	194 °F
Antistatic fabric	No	х- х-			
Flame retardant	No	X- X-			
Lateral stable	Yes	¥:	Minimum	-15 °C	5 °F
Color	green				

Last modification on: 23-12-2010