



Belt Construction

Type 3-ply
beige

| Fabric | | |
|--------------------|---------------------|---|
| Number of fabrics | | 3 |
| Fabric top layer | Polyester or cotton | P |
| Fabric inner layer | Polyester or cotton | P |
| Fabric bottom side | Polyester or cotton | P |

| Cover | | | Bottomside | | |
|-------------------------------|------|--------|-----------------------|------|--------|
| Thickness cover | 0 mm | 0 inch | Thickness bottom side | 0 mm | 0 inch |
| Material top side | | Fabric | Material bottom side | | Fabric |
| Profile top side | | - | Profile bottom side | | - |
| Hardness top layer (° ShoreA) | | 0 | | | |

Technical data

| | | | | | |
|---------------------------------|---------------------|-------------------------|---------------------------------|--------|---------------|
| Coefficient of friction (steel) | | 0,2 | Tension force for 1% elongation | 2 N/mm | 11,4 lbf/inch |
| Thickness | 1,7 mm | 0,067 inch | Maximum tension | 6 N/mm | 34,3 lbf/inch |
| Weight | 2 kg/m ² | 0,41 lb/ft ² | Maximum strain | | 2 % |
| Recommended tension | N/mm | lbf/inch | | | |
| Recommended tension: strain | | 0,4-0,7 % | | | |


RoI

| | | | | |
|------------------------|-----|-------------------------------------|-------|-------------|
| Carrying rollers | Yes | Minimum pulley diameter flection | 25 mm | 0,9843 inch |
| Slider bed | Yes | Minimum pulley diameter contraflect | 35 mm | 1,378 inch |
| Throughed installation | Yes | | | |

International standards

| | | | |
|------------------|-----|------------------|----|
| FDA conformance | Yes | EU conformance | No |
| USDA conformance | No | ATEX conformance | No |

Properties

| | | | | | |
|--------------------------|-------|---|---------|--------|--------|
| Oil and grease resistant | |  | Maximum | 121 °C | 250 °F |
| Antistatic cover | No | | Minimum | -40 °C | -40 °F |
| Antistatic fabric | No | | | | |
| Flame retardant | No | | | | |
| Lateral stable | No | | | | |
| Color | beige | | | | |

Joint data for hot press

| | | | | |
|----------|-------|-------------------------------------|------|------|
| Pressure | 0 Bar | Temperature presselement topside | 0 °C | 0 °F |
| | | Temperature presselement bottomside | 0 °C | 0 °F |
| | | Temperature thermocouple | 0 °C | 0 °F |

Last modification on: 16-02-2017

The information contained in this document is based on trials under standard conditions carried out by Research Centres and data selected from the literature, but shall in no event be held to constitute or imply any warranty, undertaking, express or implied commitment from our part. New knowledge and experiences can lead to modifications and changes within a short time without prior notice. No liability whatsoever can be accepted by Bandtransport Europe B.V. with regard to the handling processing or use of the product or products concerned which much in all cases be employed in accordance with all relevant laws and/or regulations in force in the country or countries concerned.