

**Belt Construction****Type UM22-75S
petrol**

Fabric	
Number of fabrics	2
Fabric top layer	Polyester monofilament, with extra lateral stability RH
Fabric inner layer	-
Fabric bottom side	Polyester monofilament, with extra lateral stability, antistatic RHA

Cover			Bottomside		
Thickness cover	0,5 mm	0,02 inch	Thickness bottom side	0,1 mm	0,004 inch
Material top side		PU	Material bottom side		Impregnated
Profile top side		Satin matt finish	Profile bottom side		-
Hardness top layer (° ShoreA)		93			

Technical data

Coefficient of friction (steel)		0,2	Tension force for 1% elongation	9 N/mm	51,4 lbf/inch
Thickness	2,5 mm	0,098 inch	Maximum tension	16 N/mm	91,4 lbf/inch
Weight	2,7 kg/m ²	0,55 lb/ft ²	Maximum strain		2 %
Recommended tension	4-7 N/mm	23-40 lbf/inch			
Recommended tension: strain		0,4-0,7 %			

Rol

Carrying rollers	Yes	Minimum pulley diameter flection	40 mm	1,57 inch
Slider bed	Yes	Minimum pulley diameter contraflect	60 mm	2,36 inch
Throughed installation	No			

International standards

FDA conformance	Yes	EU conformance	Yes
USDA conformance	Yes	ATEX conformance	No

Properties

Oil and grease resistant	Yes		Maximum	80 °C	176 °F
Antistatic cover	No		Minimum	-10 °C	14 °F
Antistatic fabric	Yes				
Flame retardant	No				
Lateral stable	Yes				
Color	petrol				

Joint data for hot press

Pressure	1,5 Bar	Temperature presselement topside	170 °C	338 °F
		Temperature presselement bottomside	170 °C	338 °F
		Temperature thermocouple	160 °C	320 °F

Last modification on: 18-01-2019

The information contained in this document is based on trials under standard conditions carried out by Research Centres and data selected from the literature, but shall in no event be held to constitute or imply any warranty, undertaking, express or implied commitment from our part. New knowledge and experiences can lead to modifications and changes within a short time without



BANDTRANSPORT EUROPE

prior notice. No liability whatsoever can be accepted by Bandtransport Europe B.V. with regard to the handling processing or use of the product or products concerned which much in all cases be employed in accordance with all relevant laws and/or regulations in force in the country or countries concerned.