

**Type 11-98 (1400) HI  
yellow**



**TECHNICAL SPECIFICATIONS**

Fabric	DIN 60001 / EN ISO 2060	Warp Weft	Polyester (PES) 1100 dtex Polyester (PES) 1670 dtex
Weave	DIN ISO 9354		Panama 3/3
Tensile strength	DIN EN ISO 1421/V1	Warp Weft	7500 N/50mm 7500 N/50mm
Tear strength	DIN 53363	Warp Weft	1200 N 1200 N
Finish			Both sides PVC
Color			Yellow
Thickness	DIN EN ISO 2286-3		1,15 mm
Total weight	DIN EN ISO 2286-2		1400 g/m <sup>2</sup>
Adhesion	DIN EN ISO 2411		120 N/5 cm
Cold resistance	DIN EN 1876-1		-20 °C
Heat resistance	IVK / Pkt. 5		+70 °C
Light fastness	DIN EN ISO 105 B02		> 6
Crack resistance	DIN 533 59 A		No cracking after 100.000 flexes
Burning behaviour	DIN 75 200 ISO 3795		Burning speed < 100 mm/min
Field of application			Impact apron, protective apron for rotary mowers, combine harvesters, rotary rakes and similar applications. Corresponds to ISO 17103 and EN 745 for blade speeds < 90 m/s